



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

April 23, 2018

Jack Hickey
Consultant
Blue Water Marine Paint
1999 Elizabeth Street
North Brunswick, NJ 08902

Subject: Label Amendment – Label modifications
Product Name: Shelter Island
EPA Registration Number: 74681-15
Application Date: April 6, 2016
Decision Number: 525856

Dear Jack Hickey:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. The next label printing of this product must use this labeling unless subsequent changes have been approved. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Page 2 of 2
EPA Reg. No. 74681-15
Decision No. 525856

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, you may contact Joe Daniels at (703) 347-8669 or via email at daniels.joseph@epa.gov.

Sincerely,



Eric Miederhoff
Product Manager 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs


Enclosure

FRONT PANEL

SHELTER ISLAND™

HIGH PERFORMANCE COPPER FREE ABLATIVE

0000
Black



- **Copper and Tin Free Ablative**
- **Controlled Wear Rate & Optimum Biocide Release**
- **Contains a Combination of Patented SCX Biocide and a High Load of Zinc Oxide**
- **Multi-Seasonal Antifouling**
- **Compatible With Aluminum Hulls**
- **Good Protection for Low to Moderate Fouling Conditions**

DANGER

FLAMMABLE: Keep Out of Reach of Children

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

One Gallon 3.785 Liters

FRONT - LEFT PANEL

ACTIVE INGREDIENT:

ZINC PYRITHIONE 4.20% (CAS No. 13463-41-7)

INERT INGREDIENTS 95.80%

TOTAL: 100.00%

EPA REG. 74681-15

EPA ESTABLISHMENT 74681-NJ-1

Contains Petroleum Distillates, xylene or xylene range aromatic solvents

STORAGE AND DISPOSAL

STORAGE

Store in a dry area away from heat and severe cold. Keep partially used container tightly sealed.

DISPOSAL

Do not contaminate water, food or feed by storage or disposal. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

MANUFACTURED BY BLUE WATER MARINE PAINT

1999 ELIZABETH STREET
NORTH BRUNSWICK, NJ 08902

1-800-628-8422

www.bluewatermarinepaint.com

BACK PANEL

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Product Description: Shelter Island is a solvent based, copper and tin free controlled wear rate antifouling which releases its biocide via a constant exposure of the film in all waters, salt, brackish and fresh water. The ablative copolymer system of Shelter Island combines a controlled wear rate with biocide release with an inherent smooth tough film. Shelter Island contains a high loading of patented SCX biocide and select zinc oxide to enhance the performance and environmental demands for use on commercial vessels of aluminum, steel and fiberglass.

Surface Preparation: Surface must always be clean, dry and properly prepared prior to painting. Failure to do so will lead to eventually blistering and/or peeling.

General Application: For use on vessels below the true waterline. Can be sprayed, rolled or in small areas, brushed.

Apply at least 2 coats for best performance, as the life of the paint is proportional to the number of coats applied.

Do not apply this product in a way that will contact adults, children or pets either directly or through drift.

Spray Drift Management: A variety of factors including weather conditions (e.g. wind direction, wind speed, temperature, relative humidity) and method of application can influence pesticide drift. The applicator must evaluate all factors and make appropriate adjustments when applying this product.

Mixing and Thinning: Shake or mix thoroughly and stir continuously while using. Thin only when necessary with Thinner 974 for roller applications and Thinner 975 for spray..

Theoretical Coverage: Depending on surface conditions, one gallon of bottom paint will usually cover over 400 square feet of surface when roll applied at 2.0-2.5 mils dry film thickness

Clean Up: Use Thinner 975 for cleaning equipment and paint brushes.

Estimated Dry Times: Bottom paints are designed for over coating after an overnight dry. Prior to launching, allow a minimum dry of overnight. If drying conditions are poor or if paint was applied too thickly, longer periods of drying will be required. . Fresh coats of paint must be thoroughly dry before over coating.

Yearly Repainting: Scrub bottom clean at haul-out. Repaint only if old paint is sound and intact; if not, remove it . If old paint is rough, grind/sand it until smooth. Spot coat any bare areas with either Barriershield Primer or on metals Bottom Protect Epoxy Primer. Allow to touch dry to over coat. Apply 2 coats of Shelter Island .

On Bare Steel: Sandblast surface to a near white metal; remove blast residue with a broom and air hose. Apply 3-4 coats of Bottom Protect Epoxy Primer. Allow to touch dry and apply 2 coats of Shelter Island

On Bare Aluminum - Sandblast as above using a non-metallic abrasive. Remove blasting dust and apply 1 coat of Blue Water Strontium Chromate Epoxy Primer. Allow to dry in accordance with specification and apply 3-4 coats of Bottom Protect Epoxy Primer. Allow to touch dry and apply two coats of Shelter Island .

On Bare Wood: If seams are not flush, fill them with seam compound. Dry several days until skin forms. Do not sand. Apply first coat of Shelter Island (reduced 10% with Thinner 974) then follow with 2 additional unreduced coats of Shelter Island .

On Bare Fiberglass: Dewax by washing with Dewaxer 973, remove dissolved wax at

once with clean paper towels or rags; repeat; sand hard to a dull finish with 80-100 grit sandpaper. Apply 3-5 coats of Bottom Protect Epoxy Primer. Allow to touch dry as above and apply 2 coats of Shelter island



PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. Corrosive. Causes irreversible eye damage or skin burns. Harmful if absorbed through skin. Do not get in eyes, on skin or on clothing. Harmful if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Wear a NIOSH approved respirator with organic vapor (OV) cartridge with any combination of N, R or P filter with NIOSH approved number prefix TC-84A or NIOSH approved power air purifying respirator with combination HE filter and NIOSH approved number prefix TC-23 or a NIOSH gas mask with organic vapor canister with NIOSH approved number TC-14G.

Users must wear chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long sleeved shirt and long pants, socks and shoes. In addition to these minimum PPE, commercial users must wear a disposable coverall with hood and chemical resistant footwear.

Follow manufacturers instructions for cleaning/maintaining Personal Protective Equipment (PPE). If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from laundry.

FIRST AID

IF IN EYES : Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.

IF ON SKIN OR CLOTHING : Take off contaminated clothing. Rinse skin

immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.

IF SWALLOWED : Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by poison control center or doctor. Do not give anything by mouth to an unconscious person.

IF INHALED : Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth to mouth, if possible. Call a poison control center or doctor immediately for further treatment advice. For additional information in case of emergency call toll free Chemtrec 1-800-424-9300. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

ENVIRONMENTAL HAZARDS

This material is toxic to birds, fish and aquatic invertebrates and may contaminate water through runoff. Do not apply directly to water by cleaning of equipment or disposal of wastes or chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of our company including surface preparation, proper application, and environmental condition. Therefore, we cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. We shall not, under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product, at the company's option.